

DIN FITTINGS

- ELBOW
- TEE
- REDUCER
- CAP





All products backed by Metleader warranty

DIN 2605

Elbow 90° ; 180°

unit:mm





DN	Dimension	Thickness Wall	90°	180°	K
			A	O	
15	21.3	2.0	27.5	55.0	38
20	26.9	2.3	28.5	57.0	42
25	33.7	2.6	38.0	76.0	55
32	42.4	2.6	47.5	95.0	69
40	48.3	2.6	57.0	114.0	81
50	60.3	2.9	76.0	152.0	106
65	73.0	2.9	95.0	190.0	132
65	76.1	2.9	95.0	190.0	133
80	88.9	3.2	114.5	229.0	159
100	114.3	3.6	152.5	305.0	210
125	139.7	4.0	190.5	381.0	260
150	168.3	4.5	228.5	457.0	313
200	219.1	6.3	305.0	610.0	415
250	273.0	6.3	381.0	762.0	518
300	323.9	7.1	457.0	914.0	619
350	355.6	8.0	533.5	1067.0	711
400	406.4	8.8	609.5	1219.0	813
450	457.2	10.0	686.0	1372.0	915
500	508.0	11.0	762.0	1524.0	1016
600	610.0	12.7	914.0	1828.0	1219

DIN 2615

Tee-01

unit:mm





DN	D1	S1	DN	D2	S2	A	B
15	21.3	2.0	15	21.3	2.0	25	25
			10	17.2	1.8		
20	26.9	2.3	20	26.9	2.3	29	29
			15	21.3	2.0		
			10	17.2	1.8		
25	33.7	2.6	25	33.7	2.6	38	38
			20	26.9	2.3		
			15	21.3	2.0		
32	42.4	2.6	32	42.4	2.6	48	48
			25	33.7			
			20	26.9	2.3		
40	48.3	2.6	40	48.3	2.6	57	57
			32	42.4			
			25	33.7			
			20	26.9	2.3		
			15	21.3	2.0		
50	60.3	2.9	50	60.3	2.9	64	64
			40	48.3	2.6		60
			32	42.4			57
			25	33.7			57
			20	26.9	2.3		45
65	73.0	2.9	65	73.0	2.9	76	76
			50	60.3	2.6		70
			40	48.3			67
			32	42.4	64		
65	76.1	2.9	65	76.1	2.9	76	76
			50	60.3			70
			40	48.3			67
			32	42.4	2.6		64
			25	33.7			57

DIN 2615

Tee-02

unit:mm





DN	D1	S1	DN	D2	S2	A	B
80	88.9	3.2	80	88.9	3.2	86	86
			65	76.1	2.9		83
			50	60.3			76
			40	48.3	2.6		73
			25	33.7	2.6		67
100	114.3	3.6	100	114.3	3.6	105	105
			80	88.9	3.2		98
			65	76.1	2.9		95
			50	60.3	2.9		89
			40	48.3	2.6		86
125	139.7	4	125	139.7	4.0	124	124
			100	114.3	3.6		117
			80	88.9	3.2		110
			65	76.1	2.9		108
			50	60.3	2.9		105
150	168.3	4.5	150	168.3	4.5	143	143
			125	139.7	4.0		136
			100	114.3	3.6		130
			80	88.9	3.2		124
			65	76.1	2.9		121
200	219.1	6.3	200	219.1	5.9	178	178
			150	168.3	4.5		168
			125	139.7	4.0		162
			100	114.3	3.6		156
			80	88.9	3.2		153
250	273.0	6.3	250	273.0	6.3	216	216
			200	219.1	5.9		203
			150	168.3	4.5		194
			125	139.7	4.0		190
			100	114.3	3.6		185
300	323.9	7.1	300	323.9	7.1	254	254
			250	273.0	6.3		240
			200	219.1	5.9		230
			150	168.3	4.5		220
			125	139.7	4.0		216

DIN 2615

Tee-03

unit:mm





DN	D1	S1	DN	D2	S2	A	B
350	355.6	8.0	350	355.6	8.0	280	280
			300	323.9	7.1		270
			250	273.0	6.3		258
			200	219.1	5.9		248
			150	168.3	4.5		238
400	406.4	8.8	400	406.4	8.8	305	305
			350	355.6	8.0		305
			300	323.9	7.1		300
			250	273.0	6.3		283
			200	219.1	5.9		273
450	457.2	10.0	450	457	9.52	343	343
			400	406.4	8.8		330
			350	355.6	8.0		330
			300	323.9	7.1		321
			250	273.0	6.3		308
			200	219.1	5.9		299
500	508.0	11	500	508	9.52	381	381
			450	457	9.52		369
			400	406.4	8.8		356
			350	355.6	8.0		356
			300	323.9	7.1		347
			250	273.0	6.3		334
			200	219.1	5.9		324
550	558.8	9.52	550	558	9.52	419	419
600	610.0	12.5	600	610	9.52	432	432
			500	508	9.52		432
			450	457	9.52		420
			400	406.4	8.8		407
			350	355.6	8.0		407
			300	323.9	7.1		397
			250	273.0	6.3		385

DIN 2616

Reducer-01

unit:mm





DN	D1	S1	DN	D2	S2	L
20	26.9	2.3	15	21.3	2	38
			10	17.2	1.8	
25	33.7	2.6	20	26.9	2.3	50
			15	21.3	2	
32	42.4	2.6	25	33.7	2.6	50
			20	26.9	2.3	
			15	21.3	2	
40	48.3	2.6	32	42.4	2.6	64
			25	33.7	2.6	
			20	26.9	2.3	
50	60.3	2.9	40	48.3	2.6	76
			32	42.4	2.6	
			25	33.7	2.6	
65	76.1	2.9	50	60.3	2.9	90
			40	48.3	2.6	
			32	42.4	2.6	
80	88.9	3.2	65	76.1	2.9	90
			50	60.3	2.9	
			40	48.6	2.6	
100	114.3	3.6	80	88.9	3.2	100
			65	76.1	2.9	
			50	60.3	2.9	
125	139.7	4	100	114.3	3.6	127
			80	88.9	3.2	
			65	76.1	2.9	
150	168.3	4.5	125	139.7	4	140
			100	114.3	3.6	
			80	88.9	3.2	

DIN 2616

Reducer-02

unit:mm




DN	D1	S1	DN	D2	S2	L
200	219.1	6.3	150	168.3	4.5	152
			125	139.7	4	
			100	114.3	3.6	
250	273.0	6.3	200	219.1	5.9	178
			150	168.3	4.5	
			125	139.7	4	
300	323.9	7.1	250	273	6.3	203
			200	219.1	5.9	
			150	168.3	4.5	
350	355.6	8	300	323.9	7.1	330
			250	273	6.3	
			200	219.1	5.9	
			150	168.3	4.5	
400	406.4	8.8	350	355.6	8	356
			300	323.9	7.1	
			250	273	6.3	
			200	219.1	5.9	
450	457.0	10	400	406.4	8.8	381
			350	355.6	8	
			300	323.9	7.1	
			250	273	6.3	
500	508.0	11	450	457	9.52	508
			400	406.4	8.8	
			350	355.6	8	
			300	323.9	7.1	
600	609.6	12.7	500	508	9.52	508
			450	457	9.52	
			400	406.4	8.8	
			350	355.6	8	

DIN 2616

Cap

unit:mm



DN	D1	S	L
15	21.3	2.0	32
20	26.9	2.3	38
25	33.7	2.6	38
32	42.4	2.6	38
40	48.3	2.6	38
50	60.3	2.9	38
65	76.1	2.9	38
80	88.9	3.2	50
100	114.3	3.6	64
1125	139.7	4.0	76
150	168.3	4.5	90
200	219.1	6.3	100
250	273.0	6.3	127
300	323.9	7.1	153
350	355.6	8.0	166
400	406.4	8.8	178
450	457.2	10.0	204
500	508.0	11.0	229
600	609.6	12.7	267